PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISH	INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)							
(51) International Patent Classification 6:		(11) International Publication Number: WO 99/09950						
A61K 7/48, 7/50, 7/06	A1 .	(43) International Publication Date: 4 March 1999 (04.03.99)						
(21) International Application Number: PCT/US9 (22) International Filing Date: 26 May 1998 (2) (30) Priority Data: 9717947.7 22 August 1997 (22.08.97)	6.05.9	BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE,						
(71) Applicant (for all designated States except US): THE TER & GAMBLE COMPANY [US/US]; One Pr. Gamble Plaza, Cincinnati, OH 45202 (US).	PRO rocter	C- IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF,						
(72) Inventors; and (75) Inventors/Applicants (for US only): ELLIOTT, Russel [GB/GB]; 24 Nobles Way, Egham, Surrey TW (GB). PHIPPS, Nicola, Jacqueline [GB/GB]; 19 Place, Green Lane, Addlestone, Surrey KT15 2U: COFFINDAFFER, Timothy, Woodrow [US/US]; 11 Lane, Loveland, OH 45145 (US).	720 9 Wyve D (GI	RJ em B).						

(54) Title: CLEANSING COMPOSITIONS

(74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217 (US).

(57) Abstract

A rinse-off liquid personal cleansing composition comprising surfactant, water and a water-insoluble oil wherein the water-insoluble oil provides a Mean Rinse Feel Value for the composition of 3.5 or less as measured by the Rinse Feel Panel Test. The personal cleansing compositions of the invention provide excellent rinse feel and skin mildness.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithusnia	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	Œ	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	ΠL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of Americ
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands .	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Bstonia	LR	Liberia	SG	Singapore		

1.

CLEANSING COMPOSITIONS TECHNICAL FIELD

The present invention relates to cleansing compositions. In particular it relates to mild personal cleansing compositions which display improved rinse feel in combination with good skin feel attributes, and foaming properties which are suitable for simultaneously cleansing and conditioning the skin and/or the hair and which may be used, for example, in the form of foam bath preparations, shower products, skin cleansers, hand, face and body cleansers, shampoos, etc.

Background Of The Invention

Mild cosmetic compositions must satisfy a number of criteria including cleansing power, foaming properties and mildness/low irritancy/good feel with respect to the skin, hair and the ocular mucosae. Skin is made up of several layers of cells which coat and protect the underlying tissue. The keratin and collagen fibrous proteins form the skeleton of its structure. The outermost of these layers, referred to as the stratum corneum. Hair similarly has a protective outer coating enclosing the hair fibre which is called the cuticle. Anionic surfactants can penetrate the stratum corneum membrane and the cuticle and, by delipidization destroy membrane integrity and loss of barrier and water retention functions. This interference with skin and hair protective membranes can lead to a rough skin feel and eye irritation and may eventually permit the surfactant to trigger immune response creating irritation.

Ideal cosmetic cleansers should cleanse the skin or hair gently, without disrupting structural lipids and/or drying the hair and skin and without irritating the ocular mucosae or leaving skin taut after frequent use. Most lathering soaps, shower and bath products, shampoos and bars fail in this respect.

Certain synthetic surfactants are known to be mild. However, a major drawback of some mild synthetic surfactant systems when formulated for shampooing or personal cleansing is that they have what can be described as a "slippy" or "non-draggy" rinse feel which is not liked by some consumers. The use of certain surfactants such as potassium laurate, on the other hand, can yield acceptable rinse feel performance but at the expense of clinical skin mildness. These two facts make the selection of suitable surfactants in the rinse feel and mildness benefit formulation process a delicate balancing act.

Thus a need exists for personal cleansing compositions which deliver a "draggy" rinse feel while at the same time having excellent skin mildness, in addition to excellent product characteristics such as lather, cleansing, stability, thickening, rheology and in-use skin feel attributes.

Certain polyalphaolefin oils are known for use in personal cleansing compositions for the skin and hair. References to the use of such oils in personal cleansing formulations are to be found in WO 97/09031, US-A-5441730, WO 94/27574, EP-A-0692244, WO 96/32092 and WO96/06596. Hydrophobically modified silicones oils are also known for use in personal cleansing compositions and are disclosed for example in JP 05-310540.

Surprisingly, it has now been found that personal cleansing compositions having a "draggy" rinse feel at the same time as having excellent mildness characteristics are provided by the combination of certain water-insoluble oils, such as certain polyalphaolefin oils or hydrophobically modified silicones oils, in combination with a water-soluble surfactant system.

Whilst not wishing to be bound by theory, the "draggy" rinse feel is considered to be associated with an increase in wet skin friction. An important mechanism for action of such oils is considered to be their ability to deposit and change the surface energy of the skin, i.e. making the skin surface more hydrophobic. During rinsing, the water film is considered to be the lubricant for the skin, and as surface hydrophobicity increases so the water film is destabilised and the surface de-wetted. As a result the water film is at first thinned and then displaced, allowing some

direct contact between the surfaces. Both changes increase friction and produce "draggy rinsing".

Summary Of The Invention

According to the present invention there is provided a rinse-off personal cleansing composition comprising water, surfactant and a water-insoluble oil wherein the water-insoluble oil provides a Mean Rinse Feel Value for the composition of 3.5 or less as measured by the Rinse Feel Panel Test.

The compositions of the present invention provide an improvement in rinse feel while at the same time being exceptionally mild to the skin.

All concentrations and ratios herein are by weight of the cleansing composition, unless otherwise specified. Surfactant chain lengths are also on a weight average chain length basis, unless otherwise specified.

Detailed Description of the Invention

The liquid cleansing compositions herein comprise water, surfactant and a water-insoluble oil wherein the water-insoluble oil provides a Mean Rinse Feel Value for the composition of 3.5 or less as measured by the Rinse Feel Panel Test described hereinbelow. Preferably the water-insoluble oil provides a Mean Rinse Feel Value for the composition of 3.25 or less, more preferably of 3.0 or less. In preferred embodiments the water-insoluble oil used herein provides a Mean Rinse Feel Value for the composition in the range of from 3.5 to 1.0.

It is to be noted that the water-insoluble oil is directly attributable to providing a "draggy" rinse feel for the compositions herein and in particular for providing a Mean Rinse Feel Value for the compositions of 3.5 or less. In other words, an equivalent composition to the compositions of the present invention but without a water-insoluble oil as defined herein would have a Mean Rinse Feel Value of greater than 3.5.

As used herein the term "rinse feel" means the feeling of the skin during the process of rinsing lather from the skin after cleansing with a cleansing composition. The type of rinse feel which is provided by the compositions of the present invention can be described by terms such as a "draggy" rinse feel, a "soap-like" rinse feel and a "non-slippery" or "non-slimy" rinse feel. Such a "draggy", "soap-like", "non-slippery" or "non-slimy" rinse feel can be detected by an increase in friction between the hand and skin during the process of rinsing lather from the skin.

As used herein the term "water-insoluble" in relation to oils as used herein is a material which is substantially insoluble in distilled water at room temperature without the addition of other adjuncts and/or ingredients such as described herein.

Suitable water-insoluble oils for use in the personal cleansing compositions of the present invention include (a) highly branched polyalphaolefins having the following formula:

$$R^2$$
 $R^1 - (-(-C - (CH_2)_n)_m - R^4$
 R^3

wherein R¹ is H or C₁-C₂₀ alkyl, R⁴ is C₁-C₂₀ alkyl, R² is H or C₁-C₂₀, and R³ is C₅-C₂₀, n is an integer from 0 to 3 and m is an integer of from 1 to 1000 and having a number average molecular weight of from about 1000 to about 25,000, preferably from about 2000 to about 6000, more preferably from about 2500 to about 4000. Preferably the polyalphaolefins of type (a) use herein have a viscosity of from about 300cst to about 50,000cst, preferably from about 1000cst to about 12,000 cst, more preferably from about 1000cst to about 4000cst at 40°C using the ASTM D-445 method for measuring viscosity. The oils of type (a) may also have a degree of unsaturation, but are preferably saturated.

Suitable polyalphaolefins of type (a) as described above can be derived from 1-alkene monomers having from about 4 to about 20 carbon atoms, preferably from about 6 to about 12 carbon atoms, especially from about 8

5

to about 12 carbon atoms. The polyalphaolefins useful herein are preferably hydrogenated polyalphaolefin polymers.

Non-limiting examples of 1-alkene monomers for use in preparing the polyalphaolefin polymers herein include 1-hexene, 1-octene, 1-decene, 1-dodecene, 1-tetradecene, branched chain isomers such as 4-methyl-1-pentene, and combinations thereof. Also suitable for preparing the polyolefin liquids are 1-hexene to 1-hexadecenes and combinations thereof, more preferably 1-octene to 1-dodecene or combinations thereof.

Examples of such oils include polydecene oils such as those commercially available from Mobil Chemical Company, P.O. Box 3140, Edison, New Jersey 08818, USA, under the tradename Puresyn 40 and Puresyn 100.

Other suitable water-insoluble oils for use herein include peralk(en)yl materials of type (b) which have the following formula:

$$R^2$$
 $R^1 - (-(-C - (CH_2)_n)_m - R^4$
 R^3

wherein R¹ is H or C₁-C₄ alkyl, R⁴ is C₁-C₄ alkyl, R² is H or C₁-C₄ alkyl or C₂-C₄ alkenyl, and R³ is H or C₁-C₄ alkyl or C₂-C₄ alkenyl, n is an integer from 0 to 3 and m is an integer of from 1 to 1000 and having a number average molecular weight of from about 600 to about 1000, preferably from about 750 to about 1000, especially from about 800 to about 1000. Preferably the branched alk(en)yl materials of type (b) have a viscosity in the range of from about 500cst to about 50,000cst, preferably from about 1000cst to about 10,000cst measured at 40°C using the ASTM method D-445 for measuring viscosity. The oils of type (b) may be unsaturated or saturated.

Suitable alk(en)yl materials of type (b) for use herein are polymers of butene, isoprene, terpene, styrene or isobutene, preferably butene or isobutene.

6

Examples of alk(en)yl oils of type (b) include polybutene oils such as those commercially available from Amoco under the tradename Indopol 40 and Indopol 100, and polyisobutene oils such as Permethyl 104A from Presperse Inc. and Parapol 950 from Exxon Chemical Inc.

Also suitable for use herein are hydrophobically modified silicones having the following formula:

$$\begin{array}{c} R' \\ R' - Si - O \\ R' \end{array} \begin{bmatrix} R \\ Si - O \\ (CH_2)_z \\ CH_3 \end{bmatrix}_x \begin{bmatrix} R \\ Si - O \\ R \end{bmatrix} \begin{bmatrix} R' \\ Si - R' \\ R' \end{bmatrix}_y$$

wherein R is C1-C4 alkyl or phenyl, R' is C1-C20 alkyl or phenyl, z is 5 to 21, and x has a number average value in the range of from about 20 to 400, y has a number average value in the range of from about 0 to about 10 and x + y lies in the range of 30 to 400. Preferred materials have values for x of from 40 to 200, preferably 60 to 100, values for y of from 0 to 5, preferably 0, and values for the sum of x and y of from 60 to 100. The alkylene chain z may be linear or branched. In addition, the silicone backbone of the hydrophobically modified silicone may contain a small degree of branching to yield a resin (eg. MDQ or MDT resins).

Examples of such oils include those hydrophobically modified silicones available from GE Silicones under the tradename SF1632 (C16-C18 alkyl methicone), and octyl and decyl methicone.

Mixtures of the above water-insoluble oils are also suitable for use herein.

Particularly preferred from the viewpoint of improving rinse feel of the composition is a highly branched polyalphaolefin material of type (a) having a number average molecular weight of from about 2500 to about 4000 and a viscosity of from about 100cst to about 4000 cst (ASTM D-445 at 45°C) such as that commercially available from Mobil under the tradename Puresyn 100.

7

In preferred embodiments the number average particle diameter for the water-insoluble oil used herein lies in the range of from about 1 to about 500 microns, preferably from about 5 to about 200 microns, more preferably from about 5 to 50 microns and especially from about 5 to 20 microns.

It is preferable for the compositions herein to provide not only a "draggy" rinse feel but also a "non-tacky" or "non-sticky" feeling on the skin on rinsing. Therefore it is preferable to use water-insoluble oils which can be described as "non-tacky". The degree of tackiness for water-insoluble oils can be measured by the Tackiness Technical Test Method detailed below.

In preferred embodiments the water-insoluble oil used herein has a Tackiness Index of 120% to Viscasil 5M (Dimethicone) or less as measured by the Tackiness Technical Test Method described herein below. More preferred are those with a Tackiness Index of 110% to Viscasil 5M (Dimethicone) or less. Especially preferred are those with a Tackiness Index of 100% to Viscasil 5M (Dimethicone) or less, especially from 1% to 100%.

Tackiness Technical Test Method

The Tackiness Technical Test Method described herein was developed using basic tack theory. The basic theory of tack is summarised in the Stefan equation which describes the viscous resistance of separation for two discs connected by a thin "squeeze film" of liquid. This is also used in other technology areas where tack assessment is critical, e.g. printing inks. Reference to basic tack theory can be found in the journal article by Phillips, J.C. and Chaing, A.C., "Low Speed Tack Measurements of Fluids and Inks", J. Applied Polymer Science, 1995, 58, 881-895.

A simplified form of the Stefan equation is shown below for the maximum force, F, applied for time, t, to separate discs having a radius r connected by a liquid film having a thickness h and viscosity η :

$$F = \underline{3.\pi.\eta r^4} \tag{1}$$

 $8.t.h^2$

From this equation, and when the surfaces are separated at a speed ν , the separation force becomes:

$$F = k.\eta.\nu \tag{2}$$

where k is a constant if h and r are fixed in a series of comparative experiments.

This is the basis for determining the relative tackiness of the oils.

The instrument used is an Instron 4301 Tensile Tester, fitted with 10N load cell and 10mm diameter smooth steel plate on the moving crosshead. The fixed lower plate is also smooth steel and has a compliant rubber spring (56N/mm) and levelling device attaching it to the instrument base. The same plates and spring assembly are used for a set of comparison measurements. The plates are brought close together and set parallel using the levelling device. The contact force is calculated for each oil to give a consistent film thickness from the equation:

$$F = 0.0726.\eta \tag{3},$$

where η is the oil viscosity in Pa.s, F is the contact force in N. The machine is set to stop at a compressive force of F. Approximately three drops of oil are placed on the bottom plate, directly below the top plate. The plates are brought together, maintaining the required force for one minute. The tensile speed to 1mm/min and the maximum force is recorded as the tackiness observation. The plates are brought together again and a total of three observations are collected. As a check for outlier observations, the range/mean for the three observations should be less than 10%. If it is not, a further three observations are collected. Three reference oils are included in each set of comparisons, and these are Indopol H100, Viscasil 5M (Dimethicone) and SF1000. The three oils cover a range of tackiness and their data are used to determine the relative tackiness of the other oils and to assess method reproducibility. In each experiment the ratio of maximum force for an oil is expressed as a

9

percentage of the value for Viscasil 5M (Dimethicone), and this is the <u>Tackiness Index</u>. When correctly set up a coefficient of variation of less than 15% is expected in these data.

The significant differences from a set of oils are determined using one way ANOVA of log transformed force data.

Results

1. Squeeze force conditions for Tack Measurement

Oil Sample	Viscosity Pa (25°C)	Squeeze Force (N for
	<u>. </u>	<u>1 min)</u>
Puresyn 100 ¹	2.90	0.23
Puresyn 401	0.77	0.06
Indopol H100 ²	21.0	1.52
Indopol H40 ²	8.4	0.61
SF1000 (Dimethicone)3	1.1	0.08
Viscasil 5M (Dimethicone) ³	5.34	039
Permethyl 104A ⁴	21.0	1.52
Decyl Methicone ³	0.98	0.07
Octyl Methicone ³	0.632	0.05

2. Mean Separation Force at a separation speed of 1 mm/min

Oil Sample	Mean Separation Force (N)	Tackiness Index to Viscasil 5M³ (Dimethicone)
Puresyn 100 ¹	2.44	84.4
Puresyn 40 ¹	1.11	38.4
Indopol H100 ²	5.93	205.2
Indopol H40 ²	4.04	139.8
SF1000 (Dimethicone) ³	1.34	46.4
Viscasil 5M (Dimethicone) ³	2.89	100.0
Permethyl 104A ⁴	6.48	224.2
Decyl Methicone ³	1.18	40.8
Octyl Methicone ³	0.90	31.1

In the statistical analysis each oil is significantly (95%) different for tackiness.

3. Tackiness Index reproducibility from five separate experiments

Oil Sample	Mean Tackiness Index to Viscasil 5M³ (Dimethicone)	Cooefficient of Variation	95% Confid Lower Limit	ence Limits Upper Limit
Indopol H100 ²	217.2	13.1	204.5	229.9
SF1000 (Dimethicone) ³	49.8	7.1	38.5	61.1

- Polyalphaolefin supplied by Mobil Chemical Co., P.O.Box 3140, Edison, New Jersey 08818, USA
- 2. Polybutene supplied by Amoco Chemical Co., 200 East Randolph Drive, Chicago, Illinois 60601-7125, USA
- 3. Supplied by GE Silicones,
- 4. Polyisobutene supplied by Presperse Inc., P.O.Box 735, South Plainfield, N.J. 07080, USA.

Particularly preferred herein from the viewpoint of providing reduced tackiness are polyalphaolefin materials of type (a) described above having the following formula:

$$R^{2}$$
 $R^{1}-(-(-C-(CH_{2})_{n})_{m}-R^{4}$
 R^{3}

wherein R^1 is H or C_1 - C_{20} alkyl, R^4 is C_1 - C_{20} alkyl, R^2 is H or C_1 - C_{20} , and R^3 is C_1 - C_{20} preferably from C_5 - C_{20} , n is an integer from 0 to 3 and m is an integer of from 1 to 1000 and having a number average molecular weight of from about 2500 to about 4000 and a viscosity of from about 1000cst to about 2000cst at 40°C using the ASTM D-445 method for

1.1

measuring viscosity, such as that available from Mobil under the tradename Puresyn 100.

The compositions herein preferably comprise from about 0.1% to about 20%, more preferably from about 0.5% to about 10%, especially from about 1% to about 5% by weight of water-insoluble oil.

Surfactant System

As a further essential feature the compositions of the present invention comprise a surfactant system of water-soluble surfactants. Water-soluble, as defined herein, means a surfactant having a molecular weight of less than about 20,000 wherein the surfactant is capable of forming a clear isotropic solution when dissolved in water at 0.2 % w/w under ambient conditions. Surfactants suitable for inclusion in compositions according to the present invention generally have a lipophilic chain length of from about 6 to about 22 carbon atoms and can be selected from anionic, nonionic, zwitterionic and amphoteric surfactants and mixtures thereof. The total level of surfactant is preferably from about 2% to about 40%, more preferably from about 3% to about 20% by weight, and especially from about 5% to about 15% by weight. The compositions preferably comprise a mixture of anionic with zwitterionic and/or amphoteric surfactants. The weight ratio of anionic surfactant: zwitterionic and/or amphoteric surfactant is in the range from about 1:10 to about 10:1, preferably from about 1:5 to about 5:1, more preferably from about 1:3 to about 3:1. Other suitable compositions within the scope of the invention comprise mixtures of anionic, zwitterionic and/or amphoteric surfactants with one or more nonionic surfactants.

The compositions of the invention can comprise a water-soluble anionic surfactant at levels from about 0.1% to about 20%, more preferably from about 0.1% to about 15%, and especially from about 1% to about 10% by weight.

Water soluble anionic surfactants suitable for inclusion in the compositions of the invention include alkyl sulfates, ethoxylated alkyl sulfates, alkyl ethoxy carboxylates, alkyl glyceryl ether sulfonates, alkyl

ethoxy glyceryl ether sulfonates, acyl methyl taurates, fatty acyl glycinates, N-acyl glutamates, acyl isethionates, alkyl sulfosuccinates, alkyl ethoxysulfosuccinates, alpha-sulfonated fatty acids, their salts and/or their esters, alkyl phosphate esters, ethoxylated alkyl phosphate esters, acyl sarcosinates and fatty acid/protein condensates, soaps such as ammonium, magnesium, potassium, triethanolamine and sodium salts of lauric acid, myristic acid and palmitic acid, acyl aspartates, alkoxy acyl amide carboxylates, (ethoxylated) alkanolamide sulfosuccinates, ethoxylated alkyl citrate sulfosuccinates, acyl ethylene diamine triacetates, acyl hydroxyethyl isethionates, acyl amide alkoxy sulfates, linear alkyl benzene sulfonates, paraffin sulfonates, alpha olefin sulfonates, alkyl alkoxy sulfates, and mixtures thereof. Alkyl and/or acyl chain lengths for these surfactants are C6-C22, preferably C12-C18 more preferably C12-C14.

Additional water-soluble anionic surfactants suitable for use in the compositions according to the present invention are the salts of sulfuric acid esters of the reaction product of 1 mole of a higher fatty alcohol and from about 1 to about 12 moles of ethylene oxide, with sodium, ammonium and magnesium being the preferred counterions. Particularly preferred are the alkyl ethoxy sulfates containing from about 2 to 6, preferably 2 to 4 moles of ethylene oxide, such as sodium laureth-2 sulfate, sodium laureth-3 sulfate, ammonium laureth-3 sulfate and magnesium sodium laureth-3.6 sulfate. In preferred embodiments, the anionic surfactant contains at least about 50% especially at least about 75% by weight of ethoxylated alkyl sulfate.

In addition to the broad range ethoxylated alkyl sulfates obtained via conventional sodium catalysed ethoxylation techniques and subsequent sulphation processes, ethoxylated alkyl sulfates obtained from narrow range ethoxylates (NREs) are also suitable water-soluble anionic surfactants for use in the present compositions. Narrow range ethoxylated alkyl sulfates suitable for use herein are selected from sulfated alkyl ethoxylates containing on average from about 1 to about 6, preferably from about 2 to about 4 and especially about 3 moles of ethylene oxide such as NRE sodium laureth-3 sulfate. NRE materials suitable for use herein contain distributions of the desired ethylene oxide (EO_n) in the ranges of from 15% to about 30% by weight of EO_n, from about 10% to about 20%

by weight of EO_{n+1} and from about 10% to about 20% by weight of EO_{n-1} . Highly preferred NRE materials contain less than about 9% by weight of ethoxylated alkyl sulfate having 7 or more moles of ethylene oxide and less than about 13% by weight of non-ethoxylated alkyl sulfate. Suitable laureth 3 sulfate NRE materials are available from Hoechst under the trade names GENAPOL ZRO Narrow Range and GENAPOL Narrow Range.

The compositions of the present invention may contain, as a water-soluble anionic surfactant alkyl ethoxy carboxylate surfactant at a level of from about 0.5% to about 15%, preferably from about 1% to about 10%, more preferably from about 1% to about 6% and especially from about 1% to about 4% by weight. Alkyl ethoxy carboxylate surfactant is particularly valuable in the compositions according to the present invention for the delivery of excellent skin mildness attributes in combination with excellent rinsing performance and desirable lather characteristics.

Alkyl ethoxy carboxylates suitable for use herein have the general formula (I):

$R^3O(CH_2CH_2O)_kCH_2COO^-M^+$

wherein R³ is a C₁₀ to C₁₆ alkyl or alkenyl group, preferably a C₁₁-C₁₅, more preferably a C₁₂-C₁₄ alkyl or C₁₂-C₁₃ alkyl group, k is an average value of ethoxylation ranging from 2 to about 7, preferably from about 3 to about 6, more preferably from about 3.5 to about 5.5, especially from about 4 to about 5, and M is a water-solubilizing cation, preferably an alkali metal, alkaline earth metal, ammonium, lower alkanol ammonium, and mono-, di-, and tri-ethanol ammonium, more preferably sodium, potassium and ammonium, most preferably sodium and ammonium and mixtures thereof with magnesium and calcium ions.

Suitable for use herein are alkyl ethoxy carboxylate surfactants having a selected distribution of alkyl chain length and/or ethoxylate. Thus, the alkyl ethoxy carboxylate surfactants suitable for use in the compositions according to the present invention may comprise a distribution of alkyl ethoxy carboxylates having different average values of \mathbb{R}^3 and/or k.

The average value of k will generally fall in the range of from about 3 to about 6 when the average R^3 is C_{11} , C_{12} , C_{13} or C_{14} . Preferred watersoluble anionic alkyl ethoxy carboxylate surfactants suitable for use herein are the C_{12} to C_{14} (average EO 3-6) ethoxy carboxylates and the C_{12} to C_{13} (average EO 3-6) ethoxy carboxylates. Suitable materials include salts of NEODOX 23-4 (RTM) available from Shell Inc. (Houston, Texas, USA) and EMPICOL (RTM) CBCS (Albright & Wilson). Highly preferred for use herein are alkyl ethoxy carboxylate surfactants wherein, when R^3 is a C_{12} - C_{14} or C_{12} - C_{13} alkyl group and the average value of k is in the range of from about 3 to about 6, more preferably from about 3.5 to about 5.5, especially from about 4 to about 5.

In preferred embodiments, the compositions are substantially soap-free, i.e. thay contain less than about 5% by weight, preferably less than about 1% by weight, especially 0% by weight of soap.

The compositions according to the present invention may additionally comprise water-soluble nonionic surfactant at levels from about 0.1% to about 20%, more preferably from about 0.1% to about 10%, and especially from about 1% to about 8% by weight. Surfactants of this class include sucrose polyester surfactants, C₁₀-C₁₈ alkyl polyglycosides and polyhydroxy fatty acid amide surfactants having the general formula (III).

The preferred N-alkyl, N-alkoxy or N-aryloxy, polyhydroxy fatty acid amide surfactants according to formula (III) are those in which R₈ is C₅-C₃₁ hydrocarbyl, preferably C₆-C₁₉ hydrocarbyl, including straight-chain and branched chain alkyl and alkenyl, or mixtures thereof and R₉ is typically, hydrogen, C₁-C₈ alkyl or hydroxyalkyl, preferably methyl, or a group of formula -R¹-O-R² wherein R¹ is C₂-C₈ hydrocarbyl including straight-chain, branched-chain and cyclic (including aryl), and is preferably C₂-C₄ alkylene, R² is C₁-C₈ straight-chain, branched-chain and cyclic hydrocarbyl including aryl and oxyhydrocarbyl, and is preferably C₁-C₄ alkyl, especially methyl, or phenyl. Z₂ is a polyhydroxyhydrocarbyl moiety having a linear hydrocarbyl chain with at

15

least 2 (in the case of glyceraldehyde) or at least 3 hydroxyls (in the case of other reducing sugars) directly connected to the chain, or an alkoxylated derivative (preferably ethoxylated or propoxylated) thereof. Z₂ preferably will be derived from a reducing sugar in a reductive ammination reaction, most preferably Z₂ is a glycityl moiety. Suitable reducing sugars include glucose, fructose, maltose, lactose, galactose, mannose, and xylose, as well as glyceraldehyde. As raw materials, high dextrose corn syrup, high fructose corn syrup, and high maltose corn syrup can be utilised as well as the individual sugars listed above. These corn syrups may yield a mix of sugar components for Z₂. It should be understood that it is by no means intended to exclude other suitable raw materials. Z2 preferably will be consisting of CH2-(CHOH)_n-CH2OH, group selected from $CH(CH_2OH)-(CHOH)_{n-1}-CH_2OH$, CH₂(CHOH)₂(CHOR')CHOH-CH2OH, where n is an integer from 1 to 5, inclusive, and R' is H or a cyclic mono- or poly-saccharide, and alkoxylated derivatives thereof. As noted, most preferred are glycityls wherein n is 4, particularly CH2-(CHOH)₄-CH₂OH.

The most preferred polyhydroxy fatty acid amide has the formula R₈(CO)N(CH₃)CH₂(CHOH)₄CH₂OH wherein R₈ is a C₆-C₁₉ straight chain alkyl or alkenyl group. In compounds of the above formula, R₈-CO-N< can be, for example, cocoamide, stearamide, oleamide, lauramide, myristamide, capricamide, palmitamide, caprylicamide, tallowamide, etc.

Exemplary non-ionic surfactants suitable for use in the compositions according to the present invention include primary amines such as cocamine (available as Adagen 160D (TM) from Witco) and alkanolamides such as cocamide MEA (available as Empilan CME (TM) from Albright and Wilson), PEG-3 cocamide, cocamide DEA (available as Empilan CDE (TM) from Albright and Wilson), lauramide MEA (available as Empilan LME (TM) from Albright and Wilson), lauramide MIPA, lauramide DEA, and mixtures thereof.

Suitable amphoteric surfactants for use herein include (a) ammonium derivatives of formula [V]:

R_1 CON(CH₂)₂NCH₂CO₂M

wherein R₁ is C₅-C₂₂ alkyl or alkenyl, R₂ is CH₂CH₂OH or CH2CO2M, M is H, alkali metal, alkaline earth metal, ammonium or alkanolammonium and R3 is CH2CH2OH or H;

aminoalkanoates of formula [VI] (b)

R₁NH(CH₂)_nCO₂M

iminodialkanoates of formula [VII]

 $R_1N[(CH_2)_mCO_2M]_2$

and iminopolyalkanoates of formula (VIII)

 $\begin{array}{c} R_1[N(CH_2)_p]_q \text{ - } N \text{ } [CH_2CO_2M]_2 \\ \hspace{0.5cm} \mid \\ CH_2CO_2M \end{array}$

wherein n, m, p, and q are numbers from 1 to 4, and R1 and M are independently selected from the groups specified above; and

mixtures thereof. (c)

Suitable amphoteric surfactants of type (a) include compounds of formula (V) in which R₁ is C₁₁H₂₃. Suitable amphoteric surfactants of type (a) are marketed under the trade name Miranol and Empigen.

In CTFA nomenclature, materials suitable for use in the present invention include cocoamphocarboxypropionate, cocoamphocarboxy propionic acid, (otherwise referred cocoamphoacetate, cocoamphodiacetate cocoamphocarboxyglycinate), sodium lauroamphoacetate (otherwise referred to as sodium lauroamphocarboxyglycinate). Specific commercial products include those sold under the trade names of Ampholak 7TX (sodium carboxy methyl tallow polypropyl amine), Empigen CDL60 and CDR 60 (Albright & Wilson), Miranol H2M Conc. Miranol C2M Conc. N.P., Miranol C2M Conc. O.P., Miranol C2M SF, Miranol CM Special, Miranol Ultra L32 and C32 (Rhône-Poulenc); Alkateric 2CIB (Alkaril Chemicals); Amphoterge W-2 (Lonza, Inc.); Monateric CDX-38, Monateric CSH-32 (Mona Industries); Rewoteric AM-2C (Rewo Chemical Group); and Schercotic MS-2 (Scher Chemicals).

It will be understood that a number of commercially-available amphoteric surfactants of this type are manufactured and sold in the form of electroneutral complexes with, for example, hydroxide counterions or with anionic sulfate or sulfonate surfactants, especially those of the sulfated C8-C18 alcohol, C8-C18 ethoxylated alcohol or C8-C18 acyl glyceride types. Preferred from the viewpoint of mildness and product stability, however, are compositions which are essentially free of (non-ethoxylated) sulfated alcohol surfactants. Note also that the concentrations and weight ratios of the amphoteric surfactants are based herein on the uncomplexed forms of the surfactants, any anionic surfactant counterions being considered as part of the overall anionic surfactant component content.

Examples of suitable amphoteric surfactants of type (b) include N-alkyl polytrimethylene poly-, carboxymethylamines sold under the trade names Ampholak X07 and Ampholak 7CX by Berol Nobel and also salts, especially the triethanolammonium salts and salts of N-lauryl-beta-amino propionic acid and N-lauryl-imino-dipropionic acid. Such materials are sold under the trade name Deriphat by Henkel and Mirataine by Rhône-Poulenc.

The compositions herein can also contain from about 0.1% to about 20%, more preferably from about 0.1% to about 10%, and especially from about 1% to about 8% by weight of a zwitterionic surfactant.

Water-soluble betaine surfactants suitable for inclusion in the compositions of the present invention include alkyl betaines of the formula $R_5R_6R_7N^+$ (CH₂)_nCO₂M and amido betaines of the formula (IX)

$$R_{6}$$
 R_{5}
 R_{5}
 R_{7}


wherein R₅ is C₅-C₂₂ alkyl or alkenyl, R₆ and R₇ are independently C₁-C₃ alkyl, M is H, alkali metal, alkaline earth metal, ammonium or alkanolammonium, and n, m are each numbers from 1 to 4. Preferred betaines include cocoamidopropyldimethylcarboxymethyl betaine, commercially available from TH Goldschmidt under the tradename Tego betaine, and laurylamidopropyldimethylcarboxymethyl betaine, commercially available from Albright and Wilson under the tradename Empigen BR and from TH Goldschmidt under the tradename Tegobetaine L10S.

Water-soluble sultaine surfactants suitable for inclusion in the compositions of the present invention include alkylamido sultaines of the formula;

$$R_2$$
 $|$
 $R_1CON(CH_2)_mN^+(CH_2)nCH(OH)CH_2SO_3^-M^+$
 $|$
 R_3

wherein R₁ is C₇ to C₂₂ alkyl or alkenyl, R₂ and R₃ are independently C₁ to C₃ alkyl, M is H, alkali metal, alkaline earth metal, ammonium or alkanolammonium and m and n are numbers from 1 to 4. Suitable for use herein is coco amido propylhydroxy sultaine which is commercially available under the tradename Mirataine CBS from Rhone-Poulenc.

Water-soluble amine oxide surfactants suitable for inclusion in the compositions of the present invention include alkyl amine oxide R5R6R7NO and amido amine oxides of the formula



wherein R₅ is C₁₁ to C₂₂ alkyl or alkenyl, R₆ and R₇ are independently C₁ to C₃ alkyl, M is H, alkali metal, alkaline earth metal, ammonium or alkanolammonium and m is a number from 1 to 4. Preferred amine oxides include cocoamidopropylamine oxide, lauryl dimethyl amine oxide and myristyl dimethyl amine oxide.

Polymeric Cationic Conditioning Agent

The compositions according to the present invention can optionally include a polymeric cationic conditioning agent. Polymeric cationic conditioning agents are valuable in the compositions according to the present invention for provision of desirable skin feel attributes. The polymeric skin conditioning agent is preferably present at a level from about 0.01% to about 5%, preferably from about 0.01% to about 3% and especially from about 0.01% to about 2% by weight.

Suitable polymers are high molecular weight materials (mass-average molecular weight determined, for instance, by light scattering, being generally from about 2,000 to about 5,000,000, preferably from about 5,000 to about 3,000,000 more preferably from 100,000 to about 1,000,000).

Representative classes of polymers include cationic guar gums, cationic polysaccharides; cationic homopolymers and copolymers derived from acrylic and/or methacrylic acid; cationic cellulose resins, quaternized cellulose ethers: cationic copolymers ethyl hydroxy dimethyldiallylammonium chloride and acrylamide and/or acrylic acid; of dimethyldiallylammonium homopolymers copolymers of dimethyl aminoethylmethacrylate and acrylamide, acrylic chloride/acrylamide copolymers, acid/dimethyldiallylammonium

quaternised vinyl pyrrolidone acrylate or methacrylate copolymers of amino alcohol, quaternized copolymers of vinyl pyrrolidone and dimethylaminoethylmethacrylamide, vinyl pyrollidone/vinyl imidazolium methochloride copolymers and polyalkylene and ethoxypolyalkylene imines; quaternized silicones, terpolymers of acrylic acid, methacrylamidopropyl trimethyl ammonium chloride and methyl acrylate, and mixtures thereof.

By way of exemplification, cationic polymers suitable for use herein include cationic guar gums such as hydroxypropyl trimethyl ammonium guar gum (d.s. of from 0.11 to 0.22) available commercially under the trade names Jaguar C-14-S(RTM) and Jaguar C-17(RTM) and also Jaguar C-16(RTM), which contains hydroxypropyl substituents (d.s. of from 0.8-1.1) in addition to the above-specified cationic groups, and quaternized hydroxy ethyl cellulose ethers available commercially under the trade names Ucare Polymer JR-30M, JR-400, LR400, Catanal (RTM) and Other suitable cationic polymers are homopolymers of dimethyldiallylammonium chloride available commercially under the trade name Merquat 100, copolymers of dimethyl aminoethylmethacrylate and acrylamide, copolymers of dimethyldiallylammonium chloride and acrylamide, available commercially under the trade names Merquat 550 acid/dimethyldiallylammonium acrylic and Merguat S, chloride/acrylamide copolymers available under the trade name Merquat terpolymers of acrylic Merquat 3331 3330. methacrylamidopropyl trimethyl ammonium chloride and methyl acrylate commercially available under the tradename Merquat 2001, quaternized vinyl pyrrolidone acrylate or methacrylate copolymers of amino alcohol available commercially under the trade name Gafquat, for example Polyquaternium 11, 23 and 28 (quaternized copolymers of vinyl pyrrolidone and dimethyl aminoethylmethacrylate - Gafquat 755N and pyrrolidone dimethyl and vinyl copolymers of quaternized pyrrolidone/vinyl vinyl HS-100), aminoethylmethacrylamide imidazolium methochloride copolymers available under the trade names Luviquat FC370, Polyquaternium 2, and polyalkyleneimines such as polyethylenimine and ethoxylated polyethylenimine. Also suitable for use herein are those cationic polymers commercially available under the tradename Aqualon N-Hance.

The compositions of the invention may also contain from about 0.1% to about 20%, preferably from about 1% to about 15%, and more preferably from about 2% to about 10% by weight of an oil derived nonionic surfactant or mixture of oil derived nonionic surfactants. Oil derived nonionic surfactants are valuable in compositions according to the invention for the provision of skin feel benefits both in use and after use. Suitable oil derived nonionic surfactants for use herein include water soluble vegetable and animal-derived emollients such as triglycerides with a polyethyleneglycol chain inserted; ethoxylated mono and di-glycerides, polyethoxylated lanolins and ethoxylated butter derivatives. One preferred class of oil-derived nonionic surfactants for use herein have the general formula (XII)

0

$RCOCH_2CH$ (OH) CH_2 (OCH $_2CH_2$) $_nOH$

wherein n is from about 5 to about 200, preferably from about 20 to about 100, more preferably from about 30 to about 85, and wherein R comprises an aliphatic radical having on average from about 5 to 20 carbon atoms, preferably from about 7 to 18 carbon atoms.

Suitable ethoxylated oils and fats of this class include polyethyleneglycol derivatives of glyceryl cocoate, glyceryl caproate, glyceryl caprylate, glyceryl tallowate, glyceryl palmate, glyceryl stearate, glyceryl laurate, glyceryl oleate, glyceryl ricinoleate, and glyceryl fatty esters derived from triglycerides, such as palm oil, almond oil, and corn oil, preferably glyceryl tallowate and glyceryl cocoate.

Suitable oil derived nonionic surfactants of this class are available from Croda Inc. (New York, USA) under their Crovol line of materials such as Crovol EP40 (PEG 20 evening primrose glyceride), Crovol EP 70 (PEG 60 evening primrose glyceride) Crovol A-40 (PEG 20 almond glyceride), Crovol A-70 (PEG 60 almond glyceride), Crovol M-40 (PEG 20 maize glyceride), Crovol M-70 (PEG 60 maize glyceride), Crovol PK-40 (PEG 12 palm kernel glyceride), and Crovol PK-70 (PEG 45 palm kernel

glyceride) and under their Solan range of materials such as Solan E, E50 and X polyethoxylated lanolins and Aqualose L-20 (PEG 24 lanolin alcohol) and Aqualose W15 (PEG 15 lanolin alcohol) available from Westbrook Lanolin. Further suitable surfactants of this class are commercially available from Sherex Chemical Co. (Dublin, Ohio, USA) under their Varonic LI line of surfactants and from Rewo under their Rewoderm line of surfactants. These include, for example, Varonic LI 48 (polyethylene glycol (n=80) glyceryl tallowate, alternatively referred to as PEG 80 glyceryl tallowate), Varonic LI 2 (PEG 28 glyceryl tallowate), Varonic LI 420 (PEG 200 glyceryl tallowate), and Varonic LI 63 and 67 (PEG 30 and PEG 80 glyceryl cocoates), Rewoderm LI5-20 (PEG-200 palmitate), Rewoderm LIS-80 (PEG-200 palmitate with PEG-7 glyceryl cocoate) and Rewoderm LIS-75 (PEG-200 palmitate with PEG-7 glyceryl cocoate) and mixtures thereof. Other oil-derived emollients suitable for use are PEG derivatives of corn, avocado, and babassu oil, as well as Softigen 767 (PEG(6) caprylic/capric glycerides).

Also suitable for use herein are nonionic surfactants derived from composite vegetable fats extracted from the fruit of the Shea Tree (Butyrospermum Karkii Kotschy) and derivatives thereof. This vegetable fat, known as Shea Butter is widely used in Central Africa for a variety of means such as soap making and as a barrier cream, it is marketed by Sederma (78610 Le Perray En Yvelines, France). Particularly suitable are ethoxylated derivatives of Shea butter available from Karlshamn Chemical Co. (Columbos, Ohio, USA) under their Lipex range of chemicals, such as Lipex 102 E-75 and Lipex 102 E-3 (ethoxylated mono, di-glycerides of Shea butter) and from Croda Inc. (New York, USA) under their Crovol line of materials such as Crovol SB-70 (ethoxylated mono, di-glycerides of Similarly, ethoxylated derivatives of Mango, Cocoa and Shea butter). Illipe butter may be used in compositions according to the invention. Although these are classified as ethoxylated nonionic surfactants it is understood that a certain proportion may remain as non-ethoxylated vegetable oil or fat.

Other suitable oil-derived nonionic surfactants include ethoxylated derivatives of almond oil, peanut oil, rice bran oil, wheat germ oil, linseed oil, jojoba oil, oil of apricot pits, walnuts, palm nuts, pistachio nuts,

sesame seeds, rapeseed, cade oil, corn oil, peach pit oil, poppyseed oil, pine oil, castor oil, soybean oil, avocado oil, safflower oil, coconut oil, hazelnut oil, olive oil, grapeseed oil, and sunflower seed oil.

Oil derived nonionic surfactants highly preferred for use herein from the viewpoint of optimum mildness and skin feel characteristics are Lipex 102-3 (RTM) (PEG-3 ethoxylated derivatives of Shea Butter) and Softigen 767 (RTM) (PEG-6 caprylic/capric glycerides).

The compositions according to the present invention can also comprise lipophilic emulsifiers as skin care actives. Suitable lipophilic skin care actives include anionic food grade emulsifiers which comprise a di-acid mixed with a monoglyceride such as succinylated monoglycerides, monostearyl citrate, glyceryl monostearate diacetyl tartrate and mixtures thereof.

Optional Ingredients

The compositions herein can additionally comprise a wide variety of optional ingredients. Non-limiting examples of such ingredients are described below.

Another water-insoluble, skin/hair care ingredient suitable for use in the foaming compositions herein is a liquid, polyol carboxylic acid ester.

The polyol ester preferred for use herein is a nonocclusive liquid or liquifiable polyol carboxylic acid ester. These polyol esters are derived from a polyol radical or moiety and one or more carboxylic acid radicals or moieties. In other words, these esters contain a moiety derived from a polyol and one or more moieties derived from a carboxylic acid. These carboxylic acid esters can also be derived from a carboxylic acid. These carboxylic acid esters can also be described as liquid polyol fatty acid esters, because the terms carboxylic acid and fatty acid are often used interchangeably by those skilled in the art.

The preferred liquid polyol polyesters employed in this invention comprise certain polyols, especially sugars or sugar alcohols, esterified with at least

four fatty acid groups. Accordingly, the polyol starting material must have at least four esterifiable hydroxyl groups. Examples of preferred polyols are sugars, including monosaccharaides and disaccharides, and sugar alcohols. Examples of monosaccharides containing four hydroxyl groups are xylose and arabinose and the sugar alcohol derived from xylose, which has five hydroxyl groups, i.e., xylitol. The monosaccharide, erythrose, is not suitable in the practice of this invention since it only contains three hydroxyl groups, but the sugar alcohol derived from erythrose, i.e., erythritol, contains four hydroxyl groups and accordingly can be used. Suitable five hydroxyl group-containing monosaccharides are galactose, fructose, and sorbose. Sugar alcohols containing six -OH groups derived from the hydrolysis products of sucrose, as well as glucose and sorbose, e.g., sorbitol, are also suitable. Examples of disaccharide polyols which can be used include maltose, lactose, and sucrose, all of which contain eight hydroxyl groups.

Preferred polyols for preparing the polyesters for use in the present invention are selected from the group consisting of erythritol, xylitol, sorbitol, glucose, and sucrose. Sucrose is especially preferred.

The polyol starting material having at least four hydroxyl groups is esterified on at least four of the -OH groups with a fatty acid containing from about 8 to about 22 carbon atoms. Examples of such fatty acids include caprylic, capric, lauric, myristic, myristoleic, palmitic, palmitoleic, stearic, oleic, ricinoleic, linoleic, linolenic, eleostearic, arachidic, arachidonic, behenic, and erucic acid. The fatty acids can be derived from naturally occurring or synthetic fatty acids; they can be saturated or unsaturated, including positional and geometrical isomers. However, in order to provide liquid polyesters preferred for use herein, at least about 50% by weight of the fatty acid incorporated into the polyester molecule should be unsaturated. Oleic and linoleic acids, and mixtures thereof, are especially preferred.

The polyol fatty acid polyesters useful in this invention should contain at least four fatty acid ester groups. It is not necessary that all of the hydroxyl groups of the polyol be esterified with fatty acid, but it is preferable that the polyester contain no more than two unesterified

hydroxyl groups. Most preferably, substantially all of the hydroxyl groups of the polyol are esterified with fatty acid, i.e., the polyol moiety is substantially completely esterified. The fatty acids esterified to the polyol molecule can be the same or mixed, but as noted above, a substantial amount of the unsaturated acid ester groups must be present to provide liquidity.

To illustrate the above points, a sucrose fatty triester would not be suitable for use herein because it does not contain the required four fatty acid ester groups. A sucrose tetra-fatty acid ester would be suitable, but is not preferred because it has more than two unesterified hydroxyl groups. A sucrose hexa-fatty acid ester would be preferred because it has no more than two unesterified hydroxyl groups. Highly preferred compounds in which all the hydroxyl groups are esterified with fatty acids include the liquid sucrose octa-substituted fatty acid esters.

The following are non-limiting examples of specific polyol fatty acid polyesters containing at least four fatty acid ester groups suitable for use in the present invention: glucose tetraoleate, the glucose tetraesters of soybean oil fatty acids (unsaturated), the mannose tetraesters of mixed soybean oil fatty acids, the galactose tetraesters of oleic acid, the arabinose tetraesters of linoleic acid, xylose tetralinoleate, galactose pentaoleate, sorbitol tetraoleate, the sorbitol hexaesters of unsaturated soybean oil fatty acids, xylitol pentaoleate, sucrose tetraoleate, sucrose pentaoletate, sucrose hexaoleate, sucrose hepatoleate, sucrose octaoleate, and mixtures thereof.

As noted above, highly preferred polyol fatty acid esters are those wherein the fatty acids contain from about 14 to about 18 carbon atoms.

The preferred liquid polyol polyesters preferred for use herein have complete melting points below about 30°C, preferably below about 27.5°C, more preferably below about 25°C. Complete melting points reported herein are measured by Differential Scanning Calorimetry (DSC).

The polyol fatty acid polyesters suitable for use herein can be prepared by a variety of methods well known to those skilled in the art. These methods include: transesterification of the polyol with methyl, ethyl or glycerol

fatty acid esters using a variety of catalysts; acylation of the polyol with a fatty acid chloride; acylation of the polyol with a fatty acid anhydride; and acylation of the polyol with a fatty acid, per se. See U.S. Patent No. 2,831,854; U.S. Patent No. 4,005,196, to Jandacek, issued January 25, 1977; U.S. Patent No. 4,005,196, to Jandacek, issued January 25, 1977.

The present compositions can also comprise an auxiliary nonionic or anionic polymeric thickening component, especially a water-soluble polymeric materials, having a molecular weight greater than about 20,000. By "water-soluble polymer" is meant that the material will form a substantially clear solution in water at a 1% concentration at 25°C and the material will increase the viscosity of the water. Examples of watersoluble polymers which may desirably be used as an additional thickening component in the present compositions, are hydroxyethylcellulose, hydroxypropyl cellulose, hydroxypropyl methylcellulose, polyethylene glycol, polyacrylamide, polyacrylic acid, polyvinyl alcohol (examples include PVA 217 from Kurary Chemical Co., Japan), polyvinyl pyrrolidone K-120, dextrans, for example Dextran purified crude Grade 2P, available from D&O Chemicals, carboxymethyl cellulose, plant exudates such as acacia, ghatti, and tragacanth, seaweed extracts such as sodium alginate, propylene glycol alginate and sodium carrageenan. Preferred as the additional thickeners for the present compositions are natural polysaccharide materials. Examples of such materials are guar gum, locust bean gum, and xanthan gum. Also suitable herein preferred is hydroxyethyl cellulose having a molecular weight of about 700,000.

Hydrotrope

The compositions according to the present invention may contain as an optional feature a hydrotrope. Suitable for use herein as hydrotropes are those well known in the art, including sodium xylene sulphonate, ammonium xylene sulphonate, sodium cumene sulphonate, short chain alkyl sulphate and mixtures thereof. Hydrotrope may be present in the compositions according to the invention at a level of from about 0.01% to about 5%, preferably from about 0.1% to about 4%, more preferably from about 0.5% to about 3% by weight. Hydrotrope, as defined herein, means,

a material which, when added to a non-dilute, water-soluble surfactant system can modify its viscosity and rheological profile.

In addition to the water-insoluble oil described above, the compositions of the invention may also include an insoluble perfume or cosmetic oil or wax or a mixture thereof at a level up to about 10%, preferably up to about 3% by weight wherein the oil or wax is insoluble in the sense of being insoluble in the product matrix at a temperature of 25°C.

Suitable insoluble cosmetic oils and waxes for use herein can be selected from water-insoluble silicones inclusive of non-volatile polyalkyl and polyaryl siloxane gums and fluids, volatile cyclic polydimethylsiloxanes, polyalkoxylated silicones, amino and quaternary ammonium modified silicones, rigid cross-linked and reinforced silicones and mixtures thereof, C₁-C₂₄ esters of C₈-C₃₀ fatty acids such as isopropyl myristate, myristyl myristate and cetyl ricinoleate, C8-C30 esters of benzoic acid, beeswax, saturated and unsaturated fatty alcohols such as behenyl alcohol, hydrocarbons such as mineral oils, petrolatum, squalane and squalene, fatty sorbitan esters (see US-A-3988255, Seiden, issued October 26th 1976), lanolin and oil-like lanolin derivatives, animal and vegetable triglycerides such as almond oil, peanut oil, wheat germ oil, rice bran oil, linseed oil, jojoba oil, oil of apricot pits, walnuts, palm nuts, pistachio nuts, sesame seeds, rapeseed, cade oil, corn oil, peach pit oil, poppyseed oil, pine oil, castor oil, soyabean oil, avocado oil, safflower oil, coconut oil, hazelnut oil, olive oil, grapeseed oil, and sunflower seed oil, and C1-C24 esters of dimer and trimer acids such as diisopropyl dimerate, diisostearylmalate, diisostearyldimerate and triisostearyltrimerate.

The viscosity of the final composition (Brookfield DV II, with Cone CP41 or CP52, 25°C, neat) is preferably at least about 500 cps, more preferably from about 1,000 to about 50,000 cps, especially from about 1,000 to about 30,000 cps, more especially from about 1,000 to about 15,000 cps.

The cleansing compositions can optionally include other hair or skin moisturizers which are soluble in the cleansing composition matrix. The preferred level of such moisturizers is from about 0.5% to about 20% by weight. In preferred embodiments, the moisturizer is selected from

essential amino acid compounds found naturally occurring in the stratum corneum of the skin and water-soluble nonpolyol nonocclusives and mixtures thereof.

Some examples of more preferred nonocclusive moisturizers are squalane, sodium pyrrolidone carboxylic acid, D-panthenol, lactic acid, L-proline, guanidine, pyrrolidone, hydrolyzed protein and other collagen-derived proteins, aloe vera gel, acetamide MEA and lactamide MEA and mixtures thereof.

The compositions herein may also include one or more suspending agents. Suitable suspending agents for use herein include any of several long chain acyl derivative materials or mixtures of such materials. Included are ethylene glycol esters of fatty acids having from about 16 to about 22 carbon atoms. Preferred are the ethylene glycol stearates, both mono and distearate, but particularly the distearate containing less than about 7% of the mono stearate. Other suspending agents found useful are alkanol amides of fatty acids, having from about 16 to 22 carbon atoms, preferably from about 16 to 18 carbon atoms. Preferred alkanol amides are stearic monoethanolamide, stearic diethanolamide, stearic monoisopropanolamide and stearic monoethanolamide stearate.

Still other suitable suspending agents are alkyl (C_{16} - C_{22}) dimethyl amine oxides such as stearyl dimethyl amino oxide and trihydroxystearin commercially available under the tradename Thixcin (RTM) from Rheox.

The suspending agent is preferably present at a level of from about 0.5% to about 5%, preferably from about 0.5% to about 3%. The suspending agents serves to assist in suspending the water-insoluble oil and may give pearlescence to the product. Mixtures of suspending agents are also suitable for use in the compositions of this invention.

Compositions according to the present invention may also include an opacifier or pearlescing agent. Such materials may be included at a level of from about 0.01% to about 5%, preferably from about 0.2% to about 1.3% by weight.

Opacifiers/pearlescers suitable for inclusion in the compositions of the present invention include: titanium dioxide, TiO₂; EUPERLAN 810 (RTM); TEGO-PEARL (RTM); long chain (C₁₆ - C₂₂) acyl derivatives such as glycol or polyethylene glycol esters of fatty acid having from about 16 to about 22 carbon atoms and up to 7 ethyleneoxy units; alkanolamides of fatty acids, having from about 16 to about 22 carbon atoms, preferably about 16 to 18 carbon atoms such as stearic monoethanolamide, stearic diethanolamide, stearic monoisopropanolamide and stearic monoethanolamide and alkyl (C₁₆ - C₂₂) dimethyl amine oxides such as stearyl dimethyl amine oxide.

In preferred compositions the opacifier/pearlescer is present in the form of crystals. In highly preferred compositions the opacifier/pearlescer is a particulate polystyrene dispersion having a particle size of from about 0.05 microns to about 0.45 microns, preferably from about 0.17 microns to about 0.3 microns, such dispersions being preferred from the viewpoint of providing optimum rheology and shear-thinning behaviour. Highly preferred is styrene acrylate copolymer and OPACFIER 680 (RTM) commercially available from Morton International.

A number of additional optional materials can be added to the cleansing compositions each at a level of from about 0.1% to about 2% by weight. Such materials include proteins and polypeptides and derivatives thereof; water-soluble or solubilizable preservatives such as DMDM Hydantoin, Germall 115, methyl, ethyl, propyl and butyl esters of hydroxybenzoic acid, EDTA, Euxyl (RTM) K400, natural preservatives such as benzyl sodium benzoate and 2alcohol, potassium sorbate and bisabalol; phenoxyethanol; other moisturizing agents such as hyaluronic acid, chitin , and starch-grafted sodium polyacrylates such as Sanwet (RTM) IM-1000, IM-1500 and IM-2500 available from Celanese Superabsorbent Materials, Portsmith, VA, USA and described in US-A-4,076,663; solvents; suitable isopropanol), Oxeco (phenoxy as anti-bacterial agents such Trichlorocarbanilide (TCC) and Triclosan and; low temperature phase modifiers such as ammonium ion sources (e.g. NH4 Cl); viscosity control agents such as magnesium sulfate and other electrolytes; colouring agents; TiO2 and TiO2-coated mica; perfumes and perfume solubilizers; and zeolites such as Valfour BV400 and derivatives thereof and Ca²⁺/Mg²⁺ sequestrants such as polycarboxylates, amino polycarboxylates, polyphosphonates, amino polyphosphonates, EDTA etc, water softening agents such as sodium citrate and insoluble particulates such as zinc stearate and fumed silica. Water is also present at a level preferably of from about 20% to about 99.89%, preferably from about 40% to about 90%, more preferably at least about 75% by weight of the compositions herein.

The pH of the compositions is preferably from about 3 to about 10, more preferably from about 5 to about 9, especially from about 5 to about 8 and most preferably from about 5 to 7.

The compositions of the present invention can be used for a variety of skin and hair care applications such as shower gels, body washes, hair shampoos, and the like.

The compositions of the present invention may be applied with the hand or preferably with a personal cleansing implement such as a puff. Suitable personal cleansing implements for use with the compositions of the present invention include those disclosed in the following patent documents which are incorporated herein by reference: US-A-5,144,744 to Campagnoli, issued September 8,1992, US-A-3,343,196 to Barnhouse, WO95/26671 to The Procter & Gamble Company, WO95/00116 to The Procter & Gamble Company and WO95/26670 to The Procter & Gamble Company.

The compositions according to the present invention are illustrated by the following non-limiting examples.

Ingredient	1/%	11/%	111/%	IV/%	V/%
Narrow Range sodium	•	•	-	- •	•
laureth-3 sulphate (Genopol ZRONR)1					
Ammonium laureth-3 sulphate (Empicol EAC TP) ²	8.4	8.4	15.0	15.0	15.0

T			-2	5.0	2.0
Ammonium lauryl	-	-		5.0	2.0
sulphate (Empicol	1				
AL30) ²		3.6	10.0		5.0
Lauroamphoacetate	3.6	3.6	10.0		. 5.5
(Empigen CDL60P) ²		0.5			•
Na Lauroyi	0.5	0.5			
Sarcosinate					
(Hamposyl L30) ³					
Lauramidopropyl	•	•	-		
betaine (Empigen		į	٠.		
BR) ²				1.0	1.0
Cocamido MEA	-	-	1.0	1.0	1.0
(Empilan CME) ²					2.0
Ethylene Glycol	2.0	2.0	2.0	2.0	2.0
Distearate (Radia					
7266)					
Trihydroxystearin	-			-	•
(Thixcin (RTM)) ⁴					
Lauric Acid	•	-			•
Dobanol 23 ⁵	0.4	0.4	 		
Water-insoluble oil ⁶	2.0	10.0	6.0	4.0	2.0
Perfume	0.5	0.5	1.0	1.0	1.5
EDTA	0.11	0.11	0.11	0.11	0.11
Benzoate	0.25	0.25	0.25	0.25	0.25
DMDM Hydantoin	0.138	0.138	0.138	0.138	0.138
Citric acid	0.7	0.7	1.5	0.4	1.0
Viscasil D5M	•		-	-	•,
(Dimethicone) ⁷					
Sodium Chloride	0.5	0.5	0.5	0.5	0.5
Water			to 100		

Ingredient	.VI/%	VII/%	VIII/%	IX/%	X/%
Narrow Range sodium	•	•	10.0	-	•
laureth-3 sulphate (Genopol					
ZRONR) ¹					<u> </u>

Ammonium laureth-3	15.0	8.5	- .	6.0	10.0
sulphate (Empicol EAC/TP) ²					-
Ammonium lauryl sulphate	5.0	2.0	-	-	
(Empicol AL30) ²					
Lauroamphoacetate	2.0	4.0	•	3.0	
(Empigen CDL60P) ²					
Na Lauroyl Sarcosinate	-	•	-	1.5	•
(Hamposyl L30) ³					
Lauramidopropyl betaine	-		5.0	-	4.0
(Empigen BR) ²	· ·				
Cocamido MEA (Empilan	1.0	-	1.0	1.0	1.0
CME)2					
Ethylene Glycol Distearate	2.0	2.0	2.0	2.0	2.0
Trihydroxystearin (Thixcin)4	-		-	•	<u> </u>
Lauric Acid	•	•		•	-
Dobanol 23 ⁵	•			0.2	-
Water-insoluble oil ⁶	8.0	4.0	2.0	4.0	4.0
Perfume	0.5	0.5	1.0	0.5	1.0
EDTA	0.11	0.11	0.11	0.11	0.11
Benzoate	0.25	0.25	0.25	0.25	0.25
DMDM Hydantoin	0.138	0.138	0.138	0.138	0.138
Citric acid	0.5	0.8	0.2	0.6	0.3
Sodium Chloride	0.5	0.5	0.5	0.5	0.5
Viscasil D5M	-		-	. .	-
(Dimethicone) ⁷					<u> </u>
Water			to 100		

Ingredient	XI/%	XIV%	XIIV%	XIV/%	XV/%
Narrow Range sodium	•	•		-	
laureth-3 sulphate (Genopol					
ZRONR) ¹		<u> </u>			

33

•		33								
Ammonium laureth-3 sulphate (Empicol EAC/TP) ²	8.4	10.0	10.0	8.0	15					
Ammonium lauryl sulphate (Empicol AL30) ²	-	-	2.0	-	5					
Lauroamphoacetate (Empigen CDL60P) ²	3.6	5.0	5.0	3.6	-					
Na Lauroyl Sarcosinate (Hamposyl L30) ³	0.5	0.5	•	0.5	<u>-</u>					
Lauramidopropyl betaine (Empigen BR) ²	-	· •	-	-	<u>.</u>					
Cocamido MEA (Empilan CME) ²	~	-	<u>.</u>	•	1.0					
Ethylene Glycol Distearate		-	_	2.0	2.0					
Trihydroxystearin (Thixcin) ⁴	1.5	1.5	1.5	-	-					
Lauric Acid	1.5	-			-					
Dobanol 23 ⁵	-	1.5	1.5	0.4	-					
Water-insoluble oil ⁶	4.0	10.0	4.0	4.0	4.0					
Perfume	1.5	0.5	1.0	0.5	1.0					
EDTA	0.11	0.11	0.11	0.11	0.11					
Benzoate	0.25	0.25	0.25	0.25	0.25					
DMDM Hydantoin	0.138	0.138	0.138	0.138	0.138					
Citric acid	0.7	0.7	0.7	0.7	0.4					
Sodium Chloride	0.5	0.5	0.5	0.5	0.5					
Viscasil D5M (Dimethicone) ⁷	•	-	-	1.0	0.5					
Water			to 100	100						

- 1. Supplied by Hoechst
- 2. Supplied by Albright & Wilson
- 3. Supplied by Hampshire Chemicals
- 4. Supplied by Rheox
- 5. Supplied by Shell Chemicals
- 6. The water-insoluble oil in each of the Examples I-XV above can be Indopol 40 and Indopol 100 supplied by Amoco Chemicals, Puresyn 100 supplied by Mobil Chemical Co., Permethyl 104A

34

supplied by Presperse, SF1632, octyl methicone or decyl methicone supplied by GE Silicones

7. Supplied by GE Silicones

Method of Manufacture

Compositions can be prepared by firstly making a premix of surfactants and a suspending agent. This premix should contain no more than 15%, by weight of total composition, of surfactant. This is done by combining the surfactants (except sarcosinate), a portion of the water, powder preservatives and the pH adjuster with mild agitation. This mixture is then heated to up to about 90°C during which time, fatty alcohol/fatty acid, the suspending agent and sodium chloride are added with agitation.

The mixture is held at high temperatures for five minutes to one hour before being cooled at a controlled rate to between 30°C to 40°C via a heat exchanger causing the suspending agent to crystallize out.

To this premix the remaining water is then added followed by the water-insoluble oil, remaining surfactant, liquid preservatives and perfume. This part of the process is done at room temperature using mild agitation to yield the preferred droplet diameter of 5 to 20 microns.

The products provide excellent rinse feel and mildness benefits together with excellent rheological attributes in storage, in dispensing and in-use, in combination with good efficacy benefits including skin conditioning, skin moisturising, good product stability, cleansing and lathering.

Rinse Feel Panel Test

In order to measure the effect of the water-insoluble oils on the rinse feel of the compositions of the invention a rinse feel panel test was carried out as described below.

The test involves an expert panel of 8 people who have been specially trained and qualified in carrying out the Rinse Feel Panel Test.

Instruments

The instruments needed for this test are as follows: Timer, 2ml syringes, Thermometer, Ballot Sheet (2 per panellist), two 20L plastic containers with taps, a sink with two draining board areas and access to a water hardness system for varying hardness', water having a flow rate of 1600-1800ml/30 seconds. (Water temperature and hardness should be controlled and recorded).

Training of panellists

Each panellist is trained to recognise three different wet skin feels - grades 0, 4 and 8 described below.

Grade 0 (Extremely Draggy)

Ivory (RTM) bar soap is used for grade 0. The water hardness is 16gpg, and the water temperature is 36±1°C. The inner forearm and both hands are wet for 5 seconds. The soap bar is lathered in one hand for 6 seconds by using fingers to rotate the bar in palm of hand using one full bar rotation per count. The resulting lather is applied to the inner forearm for 10 rubs in 10 seconds (1 rub = wrist to elbow to wrist) using moderate pressure. The lather is left on the forearm for 30 seconds and the product is rinsed from the hands. The forearm is rinsed under running water for 30 seconds with the flow of water starting at the elbow. After 30 seconds the arm is stroked once from elbow to wrist using light pressure ensuring that this completed below where the water flow starts. The rinse feel experienced represents grade 0.

Grade 4 (Slightly slippery and slightly draggy)

Zest White Water Fresh (RTM) soap syndet bar (commercially available in the US) is used for grade 4. The water hardness is 16gpg, and the water temperature is $36\pm1^{\circ}$ C. The inner forearm and both hands are wet for 5 seconds. The soap bar is lathered in the hands for 6 seconds using one full bar rotation per count. The resulting lather is applied to the inner forearm for 10 rubs in 10 seconds (1 rub = wrist to elbow to wrist) using moderate pressure. The lather is left on the forearm for 30 seconds and the product is rinsed from the hands. The forearm is rinsed under running water for 10 seconds with the flow of water starting at the elbow. After 10 seconds the arm is stroked once from elbow to wrist using light pressure ensuring that this completed below where the water flow starts. The rinse feel experienced represents grade 4.

Grade 8 (Extremely Slippery)


Oil of Olay (RTM) Moisturising Body Wash (commercially available in the US) is used for grade 8. The water hardness is 3gpg, and the water temperature is 36±1°C. The inner forearm and both hands are wet for 5 seconds. 1.7ml of product is applied into wet hands. The product is lathered in the hands by rubbing palms together in a circular motion for 6 rotations in 6 seconds using one full rotation per count. The resulting lather is applied to the inner forearm for 10 rubs in 10 seconds (1 rub = wrist to elbow to wrist) using moderate pressure. The lather is left on the forearm for 30 seconds and the product is rinsed from the hands. The forearm is rinsed under running water and immediately the arm is stroked once from elbow to wrist using light pressure ensuring that this completed below where the water flow starts. The rinse feel experienced represents grade 8.

Oualification of Panellists

In order to qualify for the rinse feel panel test the panellists must carry out the following qualification test successfully.

SUBSTITUTE SHEET (RULE 26)

The inner forearm and both hands are wet for 5 seconds. 1.7ml of each product to be graded is applied to wet hands and lathered by rubbing palms together in a circular motion for 6 rotations in 6 seconds (one full rotation per count). The lather is applied to the inner forearm for 10 rubs in 10 seconds (1 rub = wrist to elbow to wrist) using moderate pressure. The lather is left on the forearm for 30 seconds. The product is rinsed from the hands. The forearm is rinsed under running water for 15 seconds with the flow of water starting at the elbow. During this time the wet skin feel will be evaluated at the following time points: 3 seconds, 9 seconds and 15 seconds. This is to be done by stroking the inner forearm from elbow to wrist three times using light pressure and starting below where the water flow starts. Rinsing is stopped after 15 seconds and each wet skin feel evaluation is marked onto the ballot sheet below:



Each panellists evaluates blind 2 sets of samples with known qualified panellists results. Each product will be run twice to confirm accuracy. If the panellist does not grade the products correctly twice in a row they have to reassess until they do. However, if after 4 attempts per product they still fail to grade correctly they must be re-trained (section I). When grading is incorrect they cannot be informed of the expected grades, they can only be told if they are too draggy or too slippery.

Each panellist must have at least 3 hours between testing each product set.

All results must be within ± 1 grade of the qualified panellists results (see table below). Once the panellists have successfully graded each product twice in a row they are qualified.

Products:

Set 1: LUX Shower Cream for Normal to Dry Skin (Taiwan) versus Taiwan Olay Moisturising Body Wash.

Set 2: Taiwan Olay Moisturising Body Wash versus US Olay Moisturising Body Wash.

Oualification Product Grades for Hard (16gpg) water

PRODUCT	3 SECONDS GRADE	9 SECONDS GRADE	15 SECONDS GRADE	
LUX	4.0	3.0	2.0	
Taiwan Olay Moisturising Body Wash	6.0	5.0	4.0	
US Olay Moisturising Body Wash	7.5	7.0	6.0	

Qualification Products for Soft (3gpg) Water:

Set 1: Safaguard Bodywash (China) versus BIORE Natural Moisture (Japan)

Set 2: LUX Shower Cream Normal (Taiwan) to Dry Skin versus US Olay Moisturising Body Wash

Oualification Product Grades in 3gpg water hardness

PRODUCT	3 SECOND GRADE	9 SECOND GRADE	15 SECOND GRADE
Safaguard Bodywash (China)	6.5±1.0	6.0±1.0	5,0±1.0
BIORE Natural Moisture	6.0±1.0	5.0±1.0	3.5±1.0
LUX Shower Cream	6.0 ± 1.0	3.5±1.0	2.0±1.0
US Olay Moisturising Body Wash	7.0±1.0	6.0±1.0	5.5±1.0

TEST EVALUATION

Two arm washes can be performed at any one time, one on each arm. Each panellist can evaluate more than one set of test samples per day, but with 3 hour intervals between each set. Moisturisers can not be applied to the forearms for 24 hours before or during the test period.

Always start on the left arm. The inner forearm and both hands are wet for 5 seconds. 1.7ml of the product to be graded is applied into wet hands. Using moderate pressure the product is lathered in the hands for 6 rotations in 6 seconds (one full rotation per second). The lather is applied to the inner forearm (from wrist to elbow to wrist) for 10 seconds using moderate pressure. The lather is left on the forearm for 30 seconds. The product is rinsed from the hands. The forearm is rinsed under running water for 15 seconds, with the flow of the water starting at the elbow. During this time the wet skin feel is evaluated at the following time points: 3 seconds, 9 seconds & 15 seconds. This is done by stroking the inner forearm from elbow to wrist three times using light pressure and starting below where the water flows onto the arm. Rinsing is stopped after 15 seconds and each wet skin feel evaluation is marked onto the ballot sheet.

Experimental Design

A randomised incomplete latin square design should be used to compare eight products using eight subjects and two treatment sites per subject.

Calculations

A statistical package capable of performing Analysis of Variance should be used (e.g. Statgraphics Plus version 2.1). The analysis should be performed at 90% significance level, using the evaluation time point as the dependant variable and product, panellist and site as the factors. For 8 subjects this design has 80% power to show differences of 0.71 grades at 90% significance.

Rinse Feel Panel Test Results

Several compositions according to the present invention were tested using the Rinse Feel Panel Test detailed above. In addition, several comparative compositions were also tested. The formulations of each product and Rinse Values are shown below.

Test Products I-IX are compositions according to the present invention.

Ingredient	I/%	11/%	111/%	IV/%	V/%	VI/%
Ammonium Laureth	8.4	8.4	8.4	8.4	8.4	8.4
Sulphate (Empicol						
EAC/TP1)				·		
Sodium	3.6	3.6	3.6	3.6	3.6	3:6
Lauroamphoacetate	ļ					
(Empigen CDL60Pl)						
Sodium Lauroyl	0.5	0.5	0.5	0.5	0.5	0.5
Sarcosinate (Hamposyl						
L30 ²)		:				
Ethylene Glycol		2	2	2	.2	2
Distearate 3						
Polyalphaolefin (Puresyn	2	4	0	0	0	0 .
1004)						
Polybutene (Indopol	0	0	2	0	0	0
H40 ⁵)						<u> </u>
Polybutene (Indopol	0	0	0	2	0	0
H100 ⁵)						
C16-C18 alkyl methicone	0	0	0	0	2 .	0
(SF1632 ⁶)						2
Polyisobutene (Permethyl	0	0	0	. 0	0	-
104A ⁷)				0.11	0.11	0.11
Tetrasodium EDTA	0.11	0.11	0.11	0.11	0.11	0.11
DMDM Hydantoin	0.138	0.138	0.138		0.138	0.138
Sodium Benzoate	0.25	0.25	0.25	0.25		0.23
Citric Acid	0.7	0.7	0.7	0.7	0.7	0.7
Perfume	0.5	0.5	0.5	0.5	0.5	
Sodium Chloride	0.5	0.5	1.4	1	1.6	1
Pareth 1213 Alcohol	0.4	0.4	0.4	0.4	0.4	0.4
(Dobanol 238)	<u> </u>		<u></u>		<u> </u>	<u></u>
Deionised Water				00	1 2.25	1 26
MEAN RINSE FEEL	3.38	2.80	1.0	1.0	3.25	1.25
VALUE				<u> </u>	<u> </u>	1

Ingredient	<u>VII/%</u>	<u>VIII/%</u>	<u>IX/%</u>
Ammonium Laureth	8.4	8.4	8.4
Sulphate (Empicol			
EAC/TP1)	·		
Sodium	3.6	3.6	3.6
Lauroamphoacetate			
(Empigen			
CDL60P1)			0.5
Sodium Lauroyl	0.5	0.5	0.5
Sarcosinate			٠.
(Hamposyl L30 ²)			
Ethylene Glycol	2	2	2
Distearate ³			
Decyl Methicone ⁶	0	4	0
Octyl Methicone ⁶	4	0	0
Puresyn 100 ⁴	0	0	4
JR30M ⁹	0	0	0.1
Tetrasodium EDTA	0.11	0.11	0.11
DMDM Hydantoin	0.138	0.138	0.138
Sodium Benzoate	0.25	0.25	0.25
Citric Acid	0.7	0.7	0.7
Perfume	0.5	0.5	0.5
Sodium Chloride	0.5	0.5	11
Pareth 1213 Alcohol	0.4	0.4	0.4
(Dobanol 238)			<u> </u>
Deionised Water		to 100	
MEAN RINSE	2.8	2.96	3.25
FEEL VALUE			<u> </u>

For comparison the following products were also tested:

Ingredient	<u>X/%</u>	<u>XI/%</u>	XII/%
Ammonium Laureth	8.4	8.4	8.4
Sulphate (Empicol			
EAC/TP ¹)			
Sodium	3.6	3.6	3.6
Lauroamphoacetate			÷
(Empigen			
CDL60P ¹)			
Sodium Lauroyl	0.5	0.5	0.5
Sarcosinate			
(Hamposyl L30 ²)			
Ethylene Glycol	2	2	. 2
Distearate ³		•	
Viscasil	2	0	0
5M ⁶ (Dimethicone)			
Puresyn 40 ⁴	0	4	0
Tetrasodium EDTA	0.11	0.11	0.11
DMDM Hydantoin	0.138	0.138	0.138
Sodium Benzoate	0.25	0.25	0.25
Citric Acid	0.7	0.7	0.7
Perfume	0.5	0.5	0.5
Sodium Chloride	0.5	0.5	0.5
Pareth 1213 Alcohol	0.4	0.4	0.4
(Dobanol 238)			
MEAN RINSE	3.94	3.63	4.2
FEEL VALUE	. 7		

For all of the above results the Standard Error on the Mean (SEM) was from 0.25 to 0.27.

- 1. Supplied by Albright & Wilson
- 2. Supplied by Hampshire Chemicals
- 3. Supplied by Saci
- 4. Supplied by Mobil Chemical Co.
- 5. Supplied by Amoco Chemical Co.
- 6. Supplied by GE Silicones

- 7.
- Supplied by Presperse Inc.
 Supplied by Shell Chemicals
 Supplied by Amerchol 8.
- 9.

Claims:

- 1. A rinse-off liquid personal cleansing composition comprising surfactant, water and a water-insoluble oil wherein the water-insoluble oil provides a Mean Rinse Feel Value for the composition of 3.5 or less as measured by the Rinse Feel Panel Test.
- 2. A personal cleansing composition according to Claim 1 wherein the composition has a Mean Rinse Feel Value of 3.25 or less.
- 3. A personal cleansing composition according to Claim 1 or 2 wherein the composition has a Mean Rinse Feel Value of 3.0 or less.
- 4. A personal cleansing composition according to any of Claims 1 to 3 comprising from about 0.5% to about 20%, preferably from about 1% to about 10% by weight of water-insoluble oil.
- 5. A personal cleansing composition according to any of Claims 1 to 4 wherein the water-insoluble oil has a tackiness index of 120% to Viscasil 5M (Dimethicone) or less as measured by the Tackiness Technical Test Method.
- 6. A personal cleansing composition according to any of Claims 1 to 5 wherein the water-insoluble oil has a tackiness index of 110% to Viscasil 5M (Dimethicone) or less as measured by the Tackiness Technical Test Method.
- 7. A personal cleansing composition according to any of Claims 1 to 6 wherein the water-insoluble oil has a tackiness index of 100% to Viscasil 5M (Dimethicone) or less as measured by the Tackiness Technical Test Method.
- 8. A personal cleansing composition according to any of Claims 1 to 7 wherein the water-insoluble oil is selected from hydrocarbon oils and hydrophobically modified silicones, and mixtures thereof.

9. A personal cleansing composition according to Claim 8 wherein the hydrocarbon oils are selected from highly branched polyalphaolefins of type (a) having the following formula:

$$R^{2}$$
 $R^{1}-(-(-C-(CH_{2})_{n})_{m}-R^{4}$
 R^{3}

wherein R¹ is H or C₁-C₂₀ alkyl, R⁴ is C₁-C₂₀ alkyl, R² is H or C₁-C₂₀, and R³ is C₅-C₂₀, n is an integer from 0 to 3 and m is an integer of from 1 to 1000 and having a number average molecular weight of from about 1000 to about 25,000.

- 10. A personal cleansing composition according to Claim 9 wherein the polyalphaolefin of type (a) has a number average molecular weight of from about 2000 to about 6000, more preferably from about 2500 to about 4000.
- 11. A personal cleansing composition according to Claim 9 or 10 wherein the polyalphaolefin of type (a) has a viscosity of from about 300cst to about 50,000cst, preferably from about 1000cst to about 12,000 cst, more preferably from about 1000cst to about 4000cst at 40°C (ASTM D-445).
- 12. A personal cleansing composition according to Claim 8 wherein the hydrocarbon oils are selected from peralk(en)yl materials of type (b) having the following formula:

$$R^{1}$$
 $-(-(-C-(CH_{2})_{n})_{m}-R^{4}$

wherein R^1 is H or C_1 - C_4 alkyl, R^4 is C_1 - C_4 alkyl, R^2 is H or C_1 - C_4 alkyl or C_2 - C_4 alkenyl, and R^3 is H or C_1 - C_4 alkyl or C_2 - C_4 alkenyl, n is an integer from 0 to 3 and m is an integer of from 1 to 1000 and having a number average molecular weight of from about

600 to about 1000, preferably from about 750 to about 1000, especially from about 800 to about 1000.

- 13. A personal cleansing composition according to Claim 12 wherein the peralk(en)yl materials of type (b) have a viscosity in the range of from about 500cst to about 50,000cst, preferably from about 1000cst to about 10,000cst measured at 40°C using the ASTM method D-445 for measuring viscosity.
- 14. A personal cleansing composition according to Claim 13 wherein the peralk(en)yl material of type (b) is a polybutene or polyisobutene.
- 15. A personal cleansing composition according to Claim 8 wherein the hydrophobically modified silicone is selected from silicones having the formula:

$$R' - Si - O = \begin{cases} R \\ Si - O \\ (CH_2)_z \\ CH_3 \end{cases} \times \begin{bmatrix} R \\ Si - O \\ R \end{bmatrix} = \begin{bmatrix} R' \\ Si - C \\ R' \end{bmatrix}$$

wherein R is C1-C4 alkyl or phenyl, R' is C1-C20 alkyl or phenyl, z is 5 to 21, and x has a number average value in the range of from about 20 to 400, y has a number average value in the range of from about 0 to about 10 and x + y lies in the range of 30 to 400.

- 16. A personal cleansing composition according to Claim 15 wherein the hydrophobically modified silicone is selected from C16-C18 alkyl methicone, octyl methicone and decyl methicone, and mixtures thereof.
- 17. A personal cleansing composition according to any of Claims 1 to 16 additionally comprising from about 1% to about 60% by weight of water-soluble surfactant selected from anionic surfactant,

nonionic, zwitterionic and amphoteric surfactants and mixtures thereof.

- 18. A personal cleansing composition according to Claim 17 wherein the water-soluble anionic surfactant is selected from alkyl sulfates, ethoxylated alkyl sulfates, alkyl glyceryl ether sulfonates, alkyl ethoxy glyceryl ether sulfonates, acyl methyl taurates, fatty acyl glycinates, alkyl ethoxy carboxylates, N-acyl glutamates, acyl isethionates, alkyl sulfosuccinates, alkyl ethoxy sulfosuccinates, alpha-sulfonated fatty acids, their salts and/or their esters, alkyl phosphates esters, ethoxylated alkyl phosphate esters, acyl sarcosinates and fatty acid/protein condensates, acyl aspartates, alkoxy acyl amide carboxylates, (ethoxylated) alkanolamide sulfosuccinates, ethoxylated alkyl citrate sulfosuccinates, acyl ethylene diamine triacetates, acyl hydroxyethyl isethionates, acyl amide alkoxy sulfates, linear alkyl benzene sulfonates, paraffin sulfonates, alkyl alkoxy sulfates, and mixtures thereof.
- 19. A personal cleansing composition according to Claim 17 or 18 wherein the water-soluble anionic surfactant ethoxylated alkyl sulfate.
- 20. A personal cleansing composition according to any of Claims 1 to 19 wherein the composition is substantially soap-free.
- 21. A personal cleansing composition according to Claim 17 wherein the water-soluble amphoteric surfactant is selected from ammonium derivatives of formula [V]:

$$R_1$$
CON(CH₂)₂NCH₂CO₂M R_3 R_2

wherein R₁ is C₅-C₂₂ alkyl or alkenyl, R₂ is CH₂CH₂OH or CH₂CO₂M, M is H, alkali metal, alkaline earth metal, ammonium or alkanolammonium and R₃ is CH₂CH₂OH or H.

22. A personal cleansing composition according to Claim 17 wherein the zwitterionic surfactant is selected from alkyl betaines of the formula R₅R₆R₇N⁺(CH₂)_nCO₂M and amido betaines of formula (IX):

$$R_{5}$$
CON (CH₂) M (CH₂) N (CH₂

wherein R₅ is C₅-C₂₂ alkyl or alkenyl, R₆ and R₇ are independently C₁-C₃ alkyl, M is H, alkali metal, alkaline earth metal, ammonium or alkanolammonium, and n, m are each numbers from 1 to 4.

- A composition according to any of Claims 1 to 22 additionally 23. comprising from about 0.01% to about 5% by weight of cationic polymeric skin conditioning agent selected from cationic guar gums, cationic polysaccharides, cationic homopolymers and copolymers derived from acrylic and/or methacrylic acid, cationic cellulose resins, quaternized hydroxy ethyl cellulose ethers, cationic copolymers of dimethyldiallylammonium chloride and acrylamide acid, cationic homopolymers and/or acrylic dimethyl dimethyldiallylammonium chloride, copolymers of aminoethylmethacrylate acrylamide, and chloride/acrylamide acid/dimethyldiallylammonium copolymers, quaternised vinyl pyrrolidone acrylate or methacrylate copolymers of amino alcohol, quaternized copolymers of vinyl pyrollidone and vinyl pyrollidone/vinyl dimethylaminoethylmethacrylamide, imidaolium methochloride copolymers and polyalkylene and ethoxypolyalkylene imines, quaternized silicones, terpolymers of acrylic acid methacrylamido propyl trimethyl ammonium chloride and methyl acrylate, and mixtures thereof.
 - 24. A personal cleansing composition according to any of Claims 1 to 23 wherein the water-insoluble oil has a number average particle diameter of from about 1 micron to about 500 microns, preferably

from about 5 microns to about 200 microns, especially from about 5 microns to about 50 microns.

A. CLASSIF	FICATION OF SUBJECT MATTER A61K7/48 A61K7/50 A61K7/00	5	
According to	International Patent Classification (IPC) or to both national classific	etion and IPC	
	SEARCHED	autralia ii o	
	cumentation searched (classification system followed by classification	on symbols)	
IPC 6	A61K		*
Documentati	ion searched other than minimum documentation to the extent that s	such documents are included in the fields see	rched
Electronic da	ata base consulted during the international search (name of data be	se and, where practical, search terms used)	
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the rei	evant passages	Relevant to claim No.
X	WO 97 14406 A (PROCTER & GAMBLE) 24 April 1997		1,4,8, 12-14,
	*		17-20, 22,23
	see the whole document		22,23
X	WO 93 09761 A (RICHARDSON VICKS 27 May 1993	INC)	1,4,8, 12,15, 17-20,
	see the whole document		22,24
X	WO 96 32919 A (PROCTER & GAMBLE) 24 October 1996		1,4,8, 15, 17-20,24
	see the whole document	• •	17 20,24
		-/	:
X Fur	ther documents are listed in the continuation of box C.	X Patent family members are listed	n annex.
* Special c	ategories of cited documents :	"T" later document published after the inte	mational filing date
	nent defining the general state of the art which is not idered to be of particular relevance	or priority date and not in conflict with cited to understand the principle or the invention	the application but eory underlying the
"E" earlier	document but published on or after the international date	"X" document of particular relevance; the cannot be considered novel or cannot	
"L" docum which	ert which may throw doubts on priority claim(s) or h is cited to establish the publication date of another on or other special reason (as specified)	involve an inventive step when the do "Y" document of particular relevance; the c cannot be considered to involve an in	cument is taken alone laimed invention
	nent referring to an oral disclosure, use, exhibition or resears	document is combined with one or moments, such combination being obvious	ore other such docu-
"P" docum	nent published prior to the international filing date but than the priority date claimed	in the art. "8" document member of the same patent	family
	e actual completion of theinternational search	Date of mailing of the international sea	rch report
	16 September 1998	24/09/1998	
Name and	t mailing address of the ISA	Authorized officer	
	European Patent Office, P.B. 5818 Patentiaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo ni, Fax: (+31-70) 340-3016	Couckuyt, P	•

I. if J. Application No PCT/US 98/10650

C.(Continu	ation) DOCUMENTS CONSIDERED TO BE RELEVANT	
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Χ .	WO 96 17592 A (PROCTER & GAMBLE) 13 June 1996	1,4,8,9, 12-14, 17-20, 22-24
	see the whole document	
X	WO 96 28140 A (PROCTER & GAMBLE) 19 September 1996	1,4,8, 12-14, 17-20, 23,24
	see the whole document	
P,X .	WO 97 35549 A (PROCTER & GAMBLE) 2 October 1997	1,4,8,9, 12-14, 17-20, 22-24
	see the whole document	
X	WO 97 03647 A (PROCTER & GAMBLE) 6 February 1997	1,4,8,9, 12-14, 17-20,22
	see the whole document	
Χ .	WO 95 05800 A (PROCTER & GAMBLE) 2 March 1995	1,4,8,9, 12-14, 17-20,22
	see the whole document	
X	EP 0 498 716 A (OREAL) 12 August 1992	1,4,8, 12-14, 17-20
	see the whole document	
X	EP 0 422 862 A (RICHARDSON VICKS INC) 17 April 1991 see the whole document	1-8, 12-14,17
X .	EP 0 336 900 A (WARNER LAMBERT CO) 11 October 1989 see the whole document	1,8
A	EP 0 435 483 A (UNILEVER PLC ;UNILEVER NV (NL)) 3 July 1991 see the whole document	1,8,15
Α	EP 0 495 596 A (DOW CORNING) 22 July 1992 see the whole document	1,8,15
Α .	EP 0 529 848 A (DOW CORNING) 3 March 1993 see the whole document	1,8,15

inte ...ional application No.

Box I	Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)
This Inte	ernational Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:
1. X	Claims Nos.: because they relate to subject matter not required to be searched by this Authority, namely: The physical characteristics "Mean Rinse Value" and the "Tackiness Index" are unusual parameters in the field of cosmetics. The search was limited to the general inventive idea of the description, examples.
2.	Claims Nos.: because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3.	Claims Nos.: because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).
Box II	Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)
This In	ternational Searching Authority found multiple inventions in this international application, as follows:
1.	As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2.	As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment
	of any additional fee.
3.	As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. [No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:
	*
Rema	rk on Protest The additional search fees were accompanied by the applicant's protest.
	No protest accompanied the payment of additional search fees.
1	

Information on patent family members

	tent document in search repon	t	Publication date		tent family ember(s)	Publication date
WO	9714406	Α	24-04-1997	NONE		<u> </u>
WO	9309761	A	27-05-1993	AU CA EP JP MX PT US US	3136593 A 2122272 A 0613369 A 7501077 T 9206741 A 101082 A 5439682 A 5599549 A 5560918 A	15-06-1993 27-05-1993 07-09-1994 02-02-1995 01-05-1993 28-02-1994 08-08-1995 04-02-1997 01-10-1996
WO	9632919	A	24-10-1996	AU CA CN EP US	5528596 A 2218683 A 1184415 A 0821579 A 5776871 A	07-11-1996 24-10-1996 10-06-1998 04-02-1998 07-07-1998
WO	9617592	A	13-06-1996	BR CA CN EP US	9509865 A 2207031 A 1169112 A 0796084 A 5674511 A	30-09-1997 13-06-1996 31-12-1997 24-09-1997 07-10-1997
WO	9628140	Α	19-09-1996	CN EP	1182361 A 0814765 A	20-05-1998 07-01-1998
WO	9735549	Α	02-10-1997	AU	2320497 A	17-10-1997
WO	9703647	Α	06-02-1997	US AU CZ EP	5607980 A 6676996 A 9800170 A 0841898 A	04-03-1997 18-02-1997 17-06-1998 20-05-1998
WO	9505800	A	02-03-1995	AU BR CA CN EP JP	7602294 A 9407633 A 2168876 A 1133557 A 0714285 A 9501934 T	21-03-1995 28-01-1997 02-03-1995 16-10-1996 05-06-1996 25-02-1997

information on patent family members

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9505800 A		US 5567428 A	22-10-1996
EP 0498716 A	12-08-1992	FR 2672209 A AT 118167 T AU 659128 B AU 1074192 A CA 2060803 A DE 69201349 D DE 69201349 T ES 2068008 T JP 5058855 A US 5324507 A	07-08-1992 15-02-1995 11-05-1995 13-08-1992 07-08-1992 23-03-1995 01-06-1995 01-04-1995 09-03-1993 28-06-1994
EP 0422862 A	17-04-1991	US 5011681 A AU 626466 B AU 6397390 A CA 2026963 A,C CN 1051671 A JP 3169804 A MX 171356 B PT 95562 A TR 25525 A	30-04-1991 30-07-1992 18-04-1991 12-04-1991 29-05-1991 23-07-1991 20-10-1993 14-08-1991 01-05-1993
EP 0336900 A	11-10-1989	US 4992476 A AU 3232589 A DK 159989 A FI 891591 A JP 2015021 A PH 25786 A PT 90198 A,B	12-02-1991 05-10-1989 05-10-1989 05-10-1989 18-01-1990 05-11-1991 10-11-1989
EP 0435483 A	03-07-1991	AT 113201 T CA 2031285 A DE 69013659 D DE 69013659 T DK 435483 T ES 2063933 T JP 4159204 A	15-11-1994 08-06-1991 01-12-1994 23-03-1995 27-02-1995 16-01-1995 02-06-1992
EP 0495596 A	22-07-1992	DE 69202707 D	06-07-1995

Information on patent family members

r. at Application No PCT/US 98/10650

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0495596 A		DE 69202707 T JP 5039216 A US 5413781 A	29-02-1996 19-02-1993 09-05-1995
EP 0529848 A	03-03-1993	US 5380527 A DE 69202739 D DE 69202739 T JP 5194183 A	10-01-1995 06-07-1995 08-02-1996 03-08-1993